

## Ashby Cross Company

## **OPTIONS**



Heated tanks with proportional control

50 RPM, electric motor driven agitators with dynamic seals allow vacuum to 2 Torr, assure uniform heat distribution, degass, and solids suspension



Vacuum pump, gauges, plumbing, regulators, and pressure vacuum valve provide a complete vacuum degas system



Sight tubes for visual level detection



Volumetric (measured) shot size controlled by encoder assures accurate, repeatable dispensing. Minimum shot size achievable is machine dependent



prevent running dry


POILIFE: ANTO-SHOT
THERE
POILIFE: ANTO-SHOT
THERE
POILIFE: MIT I - MOTO-SHOT TIME (DOL'X RECORDS)

POIL IFE TIMER

Pot life timer prevents material from curing in the mixer

Ashby Cross Company
28 Parker Street, Newburyport, MA 01950
978-463-0202 www.ashbycross.com

## **Options**




Hand-held dispense gun brings the adhesive to the work - allows greater flexibility



Remote Tank Fill

Portable cart adds flexibility in production layout - simplifies maintenance - consolidates all components onto one platform

## **Feed Systems**




55-Gallon transfer pump



55-Gallon transfer pump with agitator and pneumatic lift



Agitated pressure tank with transfer pump





55-Gallon ram inducted pump used with paste and high viscosity materials

